



# Product Spec Sheet

- Installation Guide
- Hardwax Oil Maintenance Guide
- Polyurethane Maintenance Guide
- Warranty Information

## WEST|WOOD ARCHITECTURAL SURFACES

### GLACIER Grey Scale Color Collection

Glacier features an elegant and warm light grey tone with a delicate pattern.



#### Specification Options for White Oak

Other species are available (see below) but may have different specifications to consider.

#### Design Elements

SPECIES	White Oak (American, European or French), Red Oak,   Walnut, Maple, Hickory, Pine & other preferred species
PATTERNS	Bordeaux, Chevron, Haddon Hall, Herringbone,   Marie Antoinette, Versailles or Custom
CUTS OF WOOD	Plain Sawn, Live Sawn, Rift Sawn,   Quarter Sawn & R&Q Sawn
GRADE QUALITY	Perfect, Clear, Select & Better, Character, Rustic & Prime
TEXTURES	Smooth, Wire Brushed, Hand Scraped,   Band Sawn, Distressed & French Bleed
PRE-TREATMENTS & STAINS	Bleach & Water Treatments, Water-Based Stains,   Aniline Dyes, Cerused, Fuming   & Other Specialty Branded Pre-Treatments
TOP COATS	Hardwax Oil, Polyurethane (Oil- & Water-Based), Wax,   Tung Oil & Moisture Cure & Conversion Varnish

#### Production Elements

CONSTRUCTION	Engineered or Solid
ENGINEERED WIDTHS	5-1/2", 6", 7", 8", 9-1/2", 10-1/4" & 12" options with   a Baltic Birch core that contains between 8 & 11   plies. Or 11-1/2", 13-1/2", 15-1/2" & 17-3/4" using   balanced Oak (Oak top and bottom) with 8 plies.
SOLID WIDTHS	4-3/8"-8",   with custom widths available upon request
ENGINEERED THICKNESSES	1/2", 5/8" & 3/4" 
SOLID THICKNESS	3/4" 
ENGINEERED LENGTHS	2'-8", 2'-10', 4'-8', 4'-10', 6'-10' & 6'-14-1/2',   depending upon the material selected
SOLID LENGTHS	1'-7", 1'-8", 2'-8", 2'-10', 3'-10', 3'-12', 6'-10', 6'-12',   with possible longer options
ENGINEERED WEAR LAYERS	3mm, 4mm, 5mm & 6mm options,   based upon material selected

info@westflooring.com | westflooring.com

Long Island // 4195 Middle Country Road, Unit 5, Calverton, NY / 631.821.8994 | NYC // 150 East 58th Street, Suite 720, New York, NY / 212.621.9120